



Fudo PAM 4.3 - API documentation

Release is not supported

Fudo Security

07.09.2021

1	About documentation	1
2	Authentication	2
3	Accounts	5
3.1	Data structures	5
3.2	Creating an account	7
3.3	Retrieving accounts list	8
3.4	Retrieving an account	9
3.5	Modifying accounts	9
3.6	Deleting an account	10
3.7	Retrieving users allowed to manage accounts	11
3.8	Granting management privileges	12
3.9	Revoking management privileges	12
3.10	Retrieving account-safe assignments list	13
3.11	Creating an account-safe assignments	14
3.12	Deleting an account-safe assignment	15
4	Users	16
4.1	Data structures	16
4.2	Creating a user	17
4.3	Retrieving users list	18
4.4	Retrieving a user	19
4.5	Modifying a user	20
4.6	Deleting a user	21
4.7	Retrieving users allowed to manage users	22
4.8	Granting management privileges	23
4.9	Revoking management privileges	23
4.10	Retrieving user-safe assignments list	24
4.11	Creating a user-safe assignment	25
4.12	Deleting a user-safe assignment	26
5	User authentication methods management	28
5.1	Listing user authentication methods	28
5.2	Creating user authentication method	29
5.3	Retrieving user authentication method	30

5.4	Deleting user authentication method	31
6	Servers	33
6.1	Data structures	33
6.2	Creating a server	35
6.3	Retrieving servers list	36
6.4	Retrieving a server	37
6.5	Modifying a server	37
6.6	Deleting a server	38
6.7	Retrieving users allowed to manage given server	39
6.8	Granting management privileges	40
6.9	Revoking management privileges	40
6.10	Listing server addresses	41
6.11	Creating a server address	42
6.12	Updating a server address	43
6.13	Deleting a server address	44
7	Safes	45
7.1	Data structures	45
7.2	Creating a safe	46
7.3	Retrieving safes list	47
7.4	Retrieving a safe	48
7.5	Modifying a safe	49
7.6	Deleting a safe	50
7.7	Retrieving users allowed to manage selected safe	50
7.8	Granting management privileges	51
7.9	Revoking management privileges	52
8	Safe members (account-safe-listener) management	53
8.1	Retrieving account-safe-listener assignments list	53
8.2	Creating account-safe-listener assignment	54
8.3	Deleting account-safe-listener assignment	55
9	Sessions management	56
9.1	Data structures	56
9.2	Retrieving sessions list	57
9.3	Retrieving session	58
9.4	Sending commands to session	59
10	Listeners	61
10.1	Data structures	61
10.2	Creating a listener	63
10.3	Retrieving listeners list	63
10.4	Retrieving a listener	64
10.5	Modifying a listener	65
10.6	Deleting a listener	66
10.7	Retrieving users allowed to manage given listener	66
10.8	Granting management privileges	67
10.9	Revoking management privileges	68
10.10	Retrieving listener-safe assignments list	68
10.11	Creating a listener-safe assignment	69
10.12	Deleting a listener-safe assignment	70

11 Password changers	72
11.1 Data structures	72
11.2 Creating a password changer	74
11.3 Retrieving password changers list	75
11.4 Retrieving a password changer	76
11.5 Modifying password changers	77
11.6 Deleting a password changer	78
11.7 Retrieving account-password changers assignments list	79
11.8 Adding a password changer to account	80
11.9 Deleting an account-password changer assignment	82
12 AAPM communication	83
13 API usage examples	84
13.1 Logging in and retrieving session key	84
13.2 Fetching users list	84
13.3 Adding a user	85
13.4 Setting user authentication method - static password	85
13.5 Setting user authentication method - SSH key	85
13.6 Fetching user authentication methods list	85
13.7 Deleting user authentication method	86
13.8 Changing user login	86
13.9 Blocking user	86

About documentation

Conventions and symbols

This section covers conventions used throughout this documentation.

italic

Uster interface elements.

example

Example value of a parameter, API method name or code example.

Note: Note. Additional information closely related with described topic, e.g. suggestion concerning given procedure step; additional conditions which have to be met.

<p>Warning: Warning. Essential information concerning system's operation. Not adhering to this information may have irreversible consequences.</p>

CHAPTER 2

Authentication

Accessing Fudo PAM data structures over API interface requires a *user* object defined in the local database. The same access rights restrictions apply to the API interface as in case of administration panel access.

Role	Access rights
user	<ul style="list-style-type: none"> • Connecting to servers through assigned safes. • Loggin to the User Portal (requires adding the user to the portal safe) • Fetching servers' passwords (requires additional access right).
service	Accessing SNMP information.
operator	<ul style="list-style-type: none"> • Logging in to the administration panel. • Browsing objects: servers, users, safes, accounts, to which the user has been assigned sufficient access permissions. • Blocking/unblocking objects: servers, users, safes, listeners, accounts, to which the user has been assigned sufficient access permissions. • Generating reports on demand and subscribing to periodic reports. • Activating/deactivating email notifications. • Viewing live and archived sessions involving objects (user, safe, account, server), to which the user has been assigned sufficient access permissions. • Converting sessions and downloading converted content involving objects (user, safe, account, server), to which the user has been assigned sufficient access permissions. • Available dashboard widgets: concurrent sessions, suspicious sessions, account alerts, active users, cluster status, concurrent sessions chart.
admin	<ul style="list-style-type: none"> • Logging in to the administration panel. • Managing objects: servers, users, safes, listeners, accounts, to which the user has been assigned sufficient access permissions. • Blocking/unblocking objects: servers, users, safes, listeners, accounts, to which the user has been assigned sufficient access permissions. • Generating reports on demand and subscribing to periodic reports. • Activating/deactivating email notifications. • Viewing live and archived sessions involving objects (user, safe, account, server), to which the user has been assigned management privileges. • Converting sessions and downloading converted content involving objects (user, safe, account, server), to which the user has been assigned sufficient access permissions. • Managing policies. • Available dashboard widgets: concurrent sessions, suspicious sessions, account alerts, active users, cluster status, concurrent sessions chart.

Role	Access rights
superadmin	<ul style="list-style-type: none">• Full access rights to objects management.• Full access rights to system configuration options.• Available dashboard widgets: concurrent sessions, suspicious sessions, account alerts, active users, cluster status, concurrent sessions chart, license, system events log.

Request

Method	POST
Path	/api/system/login
Headers	Content-Type: Application/JSON
Body	<pre>{ username: username, password: password }</pre>

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	<pre>{ sessionid: ygmd2env50zgr2nblypmrfcvarggn0uf }</pre>

Response

Status	401 UNAUTHORIZED
--------	------------------

Account defines the privileged account existing on the monitored server. It specifies the actual login credentials, user authentication mode: anonymous (without user authentication), regular (with login credentials substitution) or forward (with login and password forwarding); password changing policy as well as the password changer itself.

3.1 Data structures

Table 1: AccountModel

Parameter	Type	Description
changer	PasswordChangerAttributes	
credentials	AccountCredentialsAttributes	required if <code>type == regular</code>
id	bigserial	object identifier
name	string	required
ocr_enabled	bool	
ocr_lang	string	
retention	int	
server_id	int	required
type	string{anonymous, forward, regular}	required

Table 2: AccountCredentialsAttributes

Parameter	Type	Description
domain	string	
login	string	
method	string{password, ssh-key, account}	required
secret	string	<ul style="list-style-type: none"> • write only • required if method == password
password_change_policy	int	write only
private_key	string	<ul style="list-style-type: none"> • write only • required if method == ssh-key
public_key	string	read only

Table 3: PasswordChangerAttributes

Parameter	Type	Description
changer_id	int	required
privileged_mode_password	string	required if changer_id in (5, 6, 7, 8) (PC_TELNET_CISCO, PC_TELNET_CISCO_ENABLE, PC_SSH_CISCO, PC_SSH_CISCO_ENABLE)
privileged_username	string	
privileged_password	string	
ssh_username	string	required if changer_id == 4 (PC_SSH_UNIX_MYSQL)
ssh_password	string	required if changer_id == 4 (PC_SSH_UNIX_MYSQL)
ssh_host	string	required if changer_id == 4 (PC_SSH_UNIX_MYSQL)
ssh_port	string	required if changer_id == 4 (PC_SSH_UNIX_MYSQL)

Table 4: AccountSafeListenerAssignment

Parameter	Type	Description
account_id	int	<ul style="list-style-type: none"> • write only • required
account	Read only	
id	int	
name	string	
listener_id	int	<ul style="list-style-type: none"> • write only • required
listener	Read only	
id	int	
name	string	

3.2 Creating an account

Request

Method	POST
Path	/api/system/accounts
Headers	Content-Type: Application/JSON
Body	AccountModel

Response

Status	201 CREATED
Headers	Content-Type: Application/JSON
Body	AccountModel
Description	Object successfully created. Resultant object's attributes are included in response body.

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Description

Validation didn't pass.

3.3 Retrieving accounts list

Request

Method

GET

Path

/api/system/accounts

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 5: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[  
  AccountModel,  
  ...  
]
```

3.4 Retrieving an account

Request

Method

GET

Path

/api/system/accounts/:account_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

AccountModel

Response

Status

404 NOT FOUND

Description

No account with given id.

3.5 Modifying accounts

Request

Method

PUT, PATCH

Path

/api/system/accounts/:account_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

AccountModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

AccountModel

Response

Status

404 NOT FOUND

Description

No account with given id.

3.6 Deleting an account

Request

Method

DELETE

Path

/api/system/accounts/:account_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Description Object with specified identifier was not found.

3.7 Retrieving users allowed to manage accounts

Request

Method

GET

Path

/api/system/accounts/:account_id/granted_users

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 6: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
  {
    'name': 'username'
    'id': 'id'
  }, ...
]
```

3.8 Granting management privileges

Request

Method

POST

Path

/api/system/accounts/:account_id/granted_users

Body

```
{
  user_id: user_id
}
```

Response

Status

201 CREATED

3.9 Revoking management privileges

Request

Method

DELETE

Path

/api/system/accounts/:account_id/granted_users/:user_id

Response

Status204 NO CONTENT

Response

Status404 NOT FOUND

3.10 Retrieving account-safe assignments list

Request

MethodGET

Path

`/api/system/accounts`

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 7: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[  
  AccountSafeAssignmentModel,  
  ...  
]
```

3.11 Creating an account-safe assignments

Request

Method

POST

Path

/api/system/safes/:safe_id/accounts

Body

AccountSafeAssignmentModel

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

Body

AccountSafeAssignmentModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status

404 NOT FOUND

3.12 Deleting an account-safe assignment

Request

Method

DELETE

Path

/api/system/safes/:safe_id/accounts/:account_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

User defines a subject entitled to connect to servers within monitored IT infrastructure. Detailed object definition (i.e. unique login and domain combination, full name, email address etc.) enables precise accountability of user actions when login and password are substituted with a shared account login credentials.

4.1 Data structures

Table 1: UserModel

Parameter	Type	Description
ad_domain	string	
blocked	bool	
email	EEmail	
external_sync	bool	
full_name	string	
language	string{en, pl, ru}	
ldap_base	string	
name	string	required
phone	string	
reason	string	
password_complexity	bool	
role	string{superadmin, admin, operator, user}	required
valid_since	string	
valid_to	DateTime	

Table 2: UserSafeAssignment

Parameter	Type	Description
password_visible	bool	
position	int	mandatory, 0 or a negative value
safe_id	int	<ul style="list-style-type: none"> • write only • required
safe		Read only
id	int	
name	string	
use_time_policy	bool	

4.2 Creating a user

Request

Method	POST
Path	/api/system/users
Headers	Content-Type: Application/JSON
Body	UserModel

Response

Status	201 CREATED
Headers	Content-Type: Application/JSON
Body	UserModel
Description	Object successfully created. Resultant object's attributes are included in response body.

Response

Status	400 BAD REQUEST
Headers	Content-Type: Application/JSON
Body	ValidationErrors
Description	Validation didn't pass.

Example:

```
curl -k -X POST -H "Content-Type:application/json" https://10.0.150.150/api/system/
↪users?sessionId=obp0r866sjrmærwti9hply0wdfvæshzp -d '{"name":"john", "role":"user",
↪"language":"en"}'
```

```
{"id":"68719476747","email":"","language":"en","qual_name":"john","is_deleted":false,
↪"blocked":false,"reason":"","name":"john","full_name":"","organization":null,"phone
↪":"","ad_domain":"","ldap_base":"","failures":0,"password_complexity":false,
↪"external_sync":false,"valid_since":"0001-01-01T00:00:00","valid_to":"9999-12-
↪31T23:59:59.999999","domain":null,"role":"user","ldap_server":null}
```

4.3 Retrieving users list

Request

Method	GET
Path	/api/system/users
pattern	Optional parameter allowing for narrowing down the users list based on user login.

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 3: Pagination parameters

page	int
page_size	int

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	[UserModel, ...]

Example:

```
curl -k -X GET -H "Content-Type:application/json" "https://10.0.150.150/api/system/
↪users?sessionid=obp0r866sjrmxrwti9hply0wdfvxshzp"

{"id":"68719476747","email":"","language":"en","qual_name":"john","is_deleted":false,
↪"blocked":false,"reason":"","name":"john","full_name":"","organization":null,"phone
↪":"","ad_domain":"","ldap_base":"","failures":0,"password_complexity":false,
↪"external_sync":false,"valid_since":"0001-01-01T00:00:00","valid_to":"9999-12-
↪31T23:59:59.999999","domain":null,"role":"user","ldap_server":null}
```

4.4 Retrieving a user

Request

Method	GET
Path	/api/system/users/user_id

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	UserModel

Response

Status

404 NOT FOUND

Description No user with given id.

Example:

```
curl -k -X GET "https://10.0.150.150/api/system/users/68719476737?
↪sessionid=0zprc420i2ofp1aznynsllo0k0eg1qcr"

{"id":"68719476737","email":null,"language":"en","qual_name":"admin","is_deleted
↪":false,"blocked":false,"reason":null,"name":"admin","full_name":null,"organization
↪":null,"phone":null,"ad_domain":null,"ldap_base":null,"failures":-1,"password_
↪complexity":false,"external_sync":false,"valid_since":"0001-01-01T00:00:00","valid_
↪to":"9999-12-31T23:59:59.999999","domain":null,"role":"superadmin","ldap_server
↪":null}
```

4.5 Modifying a user

Request

Method

PUT, PATCH

Path

/api/system/users/user_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

UserModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

UserModel

Response

Status

404 NOT FOUND

Description No user with given id.

Example:

```
curl -k -X PATCH -H "Content-Type:application/json" https://10.0.150.150/api/system/
↪users/68719476745?sessionId=qd06m9h1b9074i107nsjzlyh5egfwhoz -d '{"name":"brian"}'

{"id":"68719476745","email":"","language":"en","qual_name":"brian","is_deleted":false,
↪"blocked":false,"reason":"","name":"brian","full_name":"","organization":null,"phone
↪":"","ad_domain":"","ldap_base":"","failures":0,"password_complexity":false,
↪"external_sync":false,"valid_since":"0001-01-01T00:00:00","valid_to":"9999-12-
↪31T23:59:59.999999","domain":null,"role":"user","ldap_server":null}
```

4.6 Deleting a user

Request

Method

DELETE

Path

/api/system/users/user_id

Response

Status

204 NO CONTENT

Response

 Status

404 NOT FOUND

 Description Object with specified identifier was not found.

Example:

```
curl -k -X DELETE https://10.0.150.150/api/system/users/68719476745?
↳sessionid=gd06m9h1b9074i107nsjzlyh5egfwhoz
```

4.7 Retrieving users allowed to manage users

Request

 Method

GET

 Path

/api/system/users/user_id/granted_users

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 4: Pagination parameters

page	int
page_size	int

Response

 Status

200 OK

 Headers

Content-Type: Application/JSON

 Body

```
[
  {
    'name': 'username',
    'id': :id
  }, ...
]
```

Example:

```
curl -k -X GET "https://10.0.150.150/api/system/users/68719476740/granted_users?
↪sessionid=gd06m9h1b9074i107nsjzlyh5egfwhoz"

[{"id":68719476748,"name":"awesome"}]
```

4.8 Granting management privileges

Request

Method

POST

Path

/api/system/users/user_id/granted_users

Body

```
{
  'user_id': :user_id
}
```

Response

Status

201 CREATED

Example:

```
curl -k -X POST -H "Content-Type:application/json" https://10.0.150.150/api/system/
↪users/68719476740/granted_users?sessionid=4ln3nd824761br03whhvjn36lila513t -d '{
↪"user_id":68719476748}'

{"id":68719476748,"name":"awesome"}
```

4.9 Revoking management privileges

Request

Method

DELETE

Path

/api/system/users/user_id/granted_users/user_id

Response

Status204 NO CONTENT

Response

Status404 NOT FOUND

Example:

```
curl -k -X DELETE https://10.0.150.150/api/system/users/68719476740/granted_
users/68719476748?sessionId=gd06m9h1b9074i107nsjzlyh5egfwhoz
```

4.10 Retrieving user-safe assignments list

Request

MethodGET

Path

/api/system/users/:user_id/safes

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 5: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
  UserSafeAssignment,
  ...
]
```

```
curl -k -X GET "https://10.0.150.150./api/system/users/68719476740/safes?sessionId=4ln3nd824761br03whhvjn36lila513t"
```

4.11 Creating a user-safe assignment

Request

Method

POST

Path

/api/system/users/:user_id/safes

Body

UserSafeAssignment

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

Body

UserSafeAssignment

Response

Status400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status404 NOT FOUND

Example:

```
curl -k -X POST -H "Content-Type:application/json" https://10.0.150.150/api/system/  
→users/68719476740/safes?sessionId=4ln3nd824761br03whhvjn36lila513t -d '{"safe_id":2,  
→ "position":0}'  
  
{  
  "safe":{  
    "id":2,"name":"portal","password_visible":false,"use_time_policy":false,  
    "position":0,"blocked":false,"valid_since":"0001-01-01T00:00:00","valid_to":"9999-  
    12-31T23:59:59.999999"}  
}
```

4.12 Deleting a user-safe assignment

Request

MethodDELETE

Path

/api/system/users/:user_id/safes/:safe_id

Response

Status204 NO CONTENT

Response

Status404 NOT FOUND

Example:

```
curl -k -X DELETE -H https://10.0.150.150/api/system/users/68719476740/safes/  
2?sessionid=jtjzjdusmc3kr7pl1ecd3kkkqcu5dytc
```

 User authentication methods management

Table 1: UserAuthenticationMethodModel

Parameter	Type	Description
position	int	required
secret	string	<ul style="list-style-type: none"> • write only • required
type	string{password, sshkey}	required

5.1 Listing user authentication methods

Request

Method	GET
Path	<code>/api/system/users/:user_id/methods</code>

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
    UserAuthenticationMethodModel,
    ...
]
```

Response

Status

404 NOT FOUND

5.2 Creating user authentication method

Request

Method

POST

Path

/api/system/users/:user_id/methods

Headers

Content-Type: Application/JSON

Body

UserAuthenticationMethodModel

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

Body

UserAuthenticationMethodModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

BodyValidationErrors

Response

Status

404 NOT FOUND

DescriptionNo user with given user_id.

5.3 Retrieving user authentication method

Request

Method

GET

Path/api/system/users/:user_id/methods/:method_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

BodyUserAuthenticationMethodModel

Response

Status404 NOT FOUND

Updating user authentication method

Request

Method

PATCH, PUT

Path

/api/system/users/:user_id/methods/:method_id

Body

UserAuthenticationMethodModel

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

UserAuthenticationMethodModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status

404 NOT FOUND

5.4 Deleting user authentication method

Request

Method

DELETE

Path

/api/system/users/:user_id/methods/:method_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Server is a definition of the IT infrastructure resource, which can be accessed over one of the specified protocols.

6.1 Data structures

Table 1: ServerModel

Parameter	Type	Description
address	IPv4/string	write only, required if subnetmask is empty (static server)
addresses	string	read only, a list of IP addresses
bind_ip	IPv4	required
blocked	bool	
description	string	object description
http	HTTPServerAttributes	
id	bigserial	object identifier
name	string	required
port	int	required
protocol	string{http, modbus, mysql, oracle, rdp, ssh, telnet, tn3270, vnc}	required
rdp	RDPAttributes	required if protocol == rdp
reason	string	reason for blocking object
subnet	SubnetModel	required if not address
tls	TLSServerAttributes	

Table 2: HTTPServerAttributes

Parameter	Type	Description
timeout	int	Default 900

Table 3: RDPServerAttributes

Parameter	Type	Description
security	string{std, tls, nla}	<ul style="list-style-type: none"> • required; • default == nla
ca_certificate	PEM	

Table 4: TLSServerAttributes

Parameter	Type	Description
ssl2	boolean	
ssl3	boolean	
ca_certificate	PEM	required if use_tls
use_tls	boolean	

Table 5: ServerAddressModel

Parameter	Type	Description
host	IPv4	required
http	HTTPServerAddressAttributes	
rdp	RDPServerAddressAttributes	
tls	TLSServerAddressAttributes	
ssh	SSHServerAddressAttributes	

Table 6: SubnetModel

Parameter	Type	Description
ip	IPv4/string	Subnetwork IP address, e.g. 10.0.255.255.
mask	int	Subnet mask in CIDR notation.

Table 7: HTTPServerAddressAttributes

Parameter	Type	Description
host	string	
tls_certificate	string	

Table 8: RDPServerAddressAttributes

Parameter	Type	Description
tls_certificate	PEM	
public_key	PEM	

Table 9: SSHServerAddressAttributes

Parameter	Type	Description
public_key	PEM	

Table 10: TLSServerAddressAttributes

Parameter	Type	Description
tls_certificate	PEM	

6.2 Creating a server

Request

Method	POST
Path	/api/system/servers
Headers	Content-Type: Application/JSON
Body	ServerModel

Response

Status	201 CREATED
Headers	Content-Type: Application/JSON
Body	ServerModel
Description	Object successfully created. Resultant object's attributes are included in response body.

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Description

Validation didn't pass.

6.3 Retrieving servers list

Request

Method

GET

Path

/api/system/servers

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 11: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
    ServerModel,
    ...
]
```


6.4 Retrieving a server

Request

Method

GET

Path

/api/system/servers/:server_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

ServerModel

Response

Status

404 NOT FOUND

Description

No server with given id.

6.5 Modifying a server

Request

Method

PUT, PATCH

Path

/api/system/servers/:server_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

ServerModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ServerModel

Response

Status

404 NOT FOUND

Description No server with given id.

6.6 Deleting a server

Request

Method

DELETE

Path

/api/system/servers/:server_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Description Object with specified identifier was not found.

6.7 Retrieving users allowed to manage given server

Request

Method

GET

Path

/api/system/servers/:server_id/granted_users

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 12: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
  {
    'name': 'username',
    'id': :id
  }, ...
]
```

6.8 Granting management privileges

Request

Method

POST

Path

/api/system/servers/:server_id/granted_users

Body

```
{
  "user_id": :user_id
}
```

Response

Status

201 CREATED

6.9 Revoking management privileges

Request

Method

DELETE

Path

/api/system/servers/:server_id/granted_users/:user_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

6.10 Listing server addresses

Request

Method

GET

Path

/api/system/servers/:server_id/addresses

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

/api/system/objects?page=3&page_size=10

Table 13: Pagination parameters

page	int
page_size	int

Response

Status

204 NO CONTENT

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
  ServerAddressModel
  ...
]
```

Response

Status

404 NOT FOUND

6.11 Creating a server address

Request

Method	POST
Path	/api/system/servers/:server_id/addresses
Headers	Content-Type: Application/JSON
Body	ServerAddressModel

Response

Status	201 CREATED
Headers	Content-Type: Application/JSON
Body	ServerAddressModel

Response

Status	400 BAD REQUEST
Headers	Content-Type: Application/JSON
Body	ValidationErrors

Response

Status

404 NOT FOUND

Description

No server with `given` :server_id.

6.12 Updating a server address

Request

Method

PATCH, PUT

Path

/api/system/servers/:server_id/addresses/:address_id

Body

ServerAddressModel

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

ServerAddressModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status

404 NOT FOUND

Description

No server with `given :server_id`.

Description

No server address with `given :address_id`

6.13 Deleting a server address

Request

Method

DELETE

Path

`/api/system/servers/:server_id/addresses/:address_id`

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Description

No server with `given :server_id`.

Description

No server address with `given :address_id`

Safe directly regulates user access to monitored servers. It specifies available protocols' features, policies and other details concerning users and servers relations.

7.1 Data structures

Table 1: SafeModel

Parameter	Type	Description
blocked	bool	
login_reason	bool	
name	string	required
rdp	SafeRDPAAttributes	
reason	string	
ssh	SafeSSHAttributes	
vnc	SafeVNCAAttributes	

Table 2: SafeRDPAAttributes

Parameter	Type	Description
audio	bool	Default true
clipboard	bool	Default true
depth	int{8,1,24,32}	Default ''
device	bool	Default true
driver_dvc	bool	Default false
multimedia	bool	Default true
resolution	Resolution	Default ''
sound	bool	Default true

Table 3: SafeSSHAttributes

Parameter	Type	Description
public_key	PEM	

Table 4: SafeVNCAttributes

Parameter	Type	Description
client_clip	bool	Default <code>true</code>
server_clip	bool	Default <code>true</code>

Table 5: UserSafeAssignment

Parameter	Type	Description
password_visible	bool	
position	int	mandatory, 0 or a negative value
safe_id	int	<ul style="list-style-type: none"> • write only • required
safe		Read only
id	int	
name	string	
use_time_policy	bool	

Table 6: AccountSafeListenerAssignment

Parameter	Type	Description
account_id	int	<ul style="list-style-type: none"> • write only • required
account		Read only
id	int	
name	string	
listener_id	int	<ul style="list-style-type: none"> • write only • required
listener		Read only
id	int	
name	string	

7.2 Creating a safe

Request

Method

POST

Path

/api/system/safes

Headers

Content-Type: Application/JSON

Body

SafeModel

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

Body

SafeModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Description Validation didn't pass.

7.3 Retrieving safes list

Request

Method

GET

Path

/api/system/safes

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 7: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
    SafeModel,
    ...
]
```

7.4 Retrieving a safe

Request

Method

GET

Path

/api/system/safes/:safe_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

SafeModel

Response

Status

404 NOT FOUND

Description

No safe with given id.

7.5 Modifying a safe

Request

Method

PUT, PATCH

Path

/api/system/safes/:safe_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

SafeModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

SafeModel

Response

Status

404 NOT FOUND

Description

No safe with given id.

7.6 Deleting a safe

Request

Method

DELETE

Path

/api/system/safes/:safe_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Description

Object with specified identifier was not found.

7.7 Retrieving users allowed to manage selected safe

Request

Method

GET

Path

/api/system/safes/:safe_id/granted_users

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

/api/system/objects?page=3&page_size=10

Table 8: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
  {
    'name': 'safename',
    'id': :id
  }, ...
]
```

7.8 Granting management privileges

Request

Method

POST

Path

/api/system/safes/:safe_id/granted_users

Body

```
{
  "user_id": :user_id
}
```

Response

Status

201 CREATED

7.9 Revoking management privileges

Request

Method

DELETE

Path

/api/system/safes/:safe_id/granted_users/:safe_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Safe members (account-safe-listener) management

8.1 Retrieving account-safe-listener assignments list

Request

Method

GET

Path

`/api/system/safes/:safe_id/account_listeners`

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 1: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[  
    AccountSafeListenerAssignment,  
    ...  
]
```

8.2 Creating account-safe-listener assignment

Request

Method

POST

Path

/api/system/safes/:safe_id/account_listeners

Body

AccountSafeListenerAssignment

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

Body

AccountSafeListenerAssignment

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status

404 NOT FOUND

8.3 Deleting account-safe-listener assignment

Request

Method

DELETE

Path

/api/system/safes/:safe_id/account_listeners/:assoc_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

9.1 Data structures

Table 1: `SessionCommandModel`

Parameter	Type	Description
command	string{kill, suspend, resume}	required

Table 2: SessionModel

Parameter	Type	Description
account		required
id	int	
name	string	
safe		Read only
id	int	
name	string	
destination_ip	IPv4	
description_port	int	
dump_mode	string{all,none,raw}	
finished_at	DateTime	
listener		
id	int	
name	string	
paused	bool	
protocol	string{http,modbus,mysql,oracle,rdp,ssh,telnet,tn3270,vnc}	
source_ip	IPv4	
source_port	int	
started_at	DateTime	
user		
id	int	
name	string	
handled_by		
login_reason	string	
reason	string	
status	string	
ocr_enabled	bool	
server_address		

9.2 Retrieving sessions list

Request

Method

GET

Path

/api/system/sessions

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 3: Pagination parameters

page	int
page_size	int

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	[SessionModel, ...]

9.3 Retrieving session

Request

Method	GET
Path	/api/system/sessions/:session_id

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	SessionModel

Response

Status

404 NOT FOUND

9.4 Sending commands to session

Request

Method

POST

Path

/api/system/sessions/:session_id/command

Body

SessionCommandModel

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

SessionCommandModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status

404 NOT FOUND

Listener determines server connection mode (proxy, gateway, transparent, bastion) as well as its specifics.

10.1 Data structures

Table 1: ListenerModel

Parameter	Type	Description
blocked	bool	
name	string	required
listen_interface	string	required if mode in (gateway, transparent)
listen_ip	IPv4	required if mode in (proxy, bastion)
listen_port	int	required if mode in (proxy, bastion)
prompt	string	
protocol	string{http, modbus, mysql, oracle, rdp, ssh, telnet, tn3270, vnc}	required
rdp	ListenerRDPAttributes	required if protocol == rdp
reason		
ssh	ListenerSSHAttributes	required if protocol == ssh
tls	ListenerTLSAttributes	

Table 2: ListenerRDPAttributes

Parameter	Type	Description
common_name	string	required if <code>secproto</code> in <code>(tls, nla)</code> and <code>tls_private_key == null</code>
security	string{std, tls, nla}	required
std_private_key	PEM	<ul style="list-style-type: none"> • write only • required if <code>secproto == std</code> • pass <code>null</code> to generate
std_public_key	PEM	Read only
tls_private_key	PEM	<ul style="list-style-type: none"> • write only • required if <code>secproto</code> in <code>(tls, nla)</code> • pass <code>null</code> to generate
tls_certificate	PEM	Read only

Table 3: ListenerSSHAttributes

Parameter	Type	Description
private_key	PEM	<ul style="list-style-type: none"> • write only • required
public_key	PEM	Read only

Table 4: ListenerTLSAttributes

Parameter	Type	Description
common_name	string	required if <code>use_tls</code> and <code>tls_private_key == null</code>
use_tls	bool	
tls_private_key	PEM	<ul style="list-style-type: none"> • write only • required if <code>use_tls</code> • pass <code>null</code> to generate
tls_certificate	PEM	Read only

Table 5: ListenerSafeAssignment

Parameter	Type	Description
listener_id	int	<ul style="list-style-type: none"> • write only • required
listener		Read only
id	int	
name	string	

10.2 Creating a listener

Request

Method	POST
Path	/api/system/listeners
Headers	Content-Type: Application/JSON
Body	ListenerModel

Response

Status	201 CREATED
Headers	Content-Type: Application/JSON
Body	ListenerModel
Description	Object successfully created. Resultant object's attributes are included in response body.

Response

Status	400 BAD REQUEST
Headers	Content-Type: Application/JSON
Body	ValidationErrors
Description	Validation didn't pass.

10.3 Retrieving listeners list

Request

Method

GET

Path

/api/system/listeners

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 6: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
    ListenerModel,
    ...
]
```

10.4 Retrieving a listener

Request

Method

GET

Path

/api/system/listeners/:listener_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

ListenerModel

Response

Status

404 NOT FOUND

Description

No listener with given id.

10.5 Modifying a listener

Request

Method

PUT, PATCH

Path

/api/system/listeners/:listener_id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

ListenerModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ListenerModel

Response

Status

404 NOT FOUND

Description

No listener with given id.

10.6 Deleting a listener

Request

Method

DELETE

Path

/api/system/listeners/:listener_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Description

Object with specified identifier was not found.

10.7 Retrieving users allowed to manage given listener

Request

Method

GET

Path

/api/system/listeners/:listener_id/granted_users

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 7: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[  
  {  
    'name': 'username',  
    'id': :id  
  }, ...  
]
```

10.8 Granting management privileges

Request

Method

POST

Path

/api/system/listeners/:listener_id/granted_users

Body

```
{
  'user_id': :user_id
}
```

Response

Status

201 CREATED

10.9 Revoking management privileges

Request

Method

DELETE

Path

/api/system/listeners/:listener_id/granted_users/:user_id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

10.10 Retrieving listener-safe assignments list

Request

Method

GET

Path

/api/system/listeners

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 8: Pagination parameters

page	int
page_size	int

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

```
[
    ListenerSafeAssignmentModel,
    ...
]
```

10.11 Creating a listener-safe assignment

Request

Method

POST

Path

/api/system/safes/:safe_id/listeners

Body

ListenerSafeAssignmentModel

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

BodyListenerSafeAssignmentModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

BodyValidationErrors

Response

Status404 NOT FOUND

10.12 Deleting a listener-safe assignment

Request

Method

DELETE

Path/api/system/safes/:safe_id/listeners/:listener_id

Response

Status204 NO CONTENT

Response

Status

404 NOT FOUND

Password changers

Account defines the privileged account existing on the monitored server. It specifies the actual login credentials, user authentication mode: anonymous (without user authentication), regular (with login credentials substitution) or forward (with login and password forwarding); password changing policy as well as the password changer itself.

11.1 Data structures

Table 1: PasswordChangerModel

Parameter	Type	Description
id	bigint	Object identifier. Read only.
name	text	Required.
changer_type	text{change,verify}	Script type. Required.
timeout	int	Script's execution time limit expressed in seconds.
transport	text{LDAP, SSH, WINRM, Telnet}	Transport layer specifier. Required.
commands	CommandsModel	Required.
variables	VariablesModel	Required.

Table 2: CommandsModel

Parameter	Type	Description
id	bigint	Object identifier. Read only.
command_type	text{EXPECTED, INPUT, DELAY, ENTER, DN, FILTER}	Specifies command type: <ul style="list-style-type: none"> • INPUT - system input. • EXPECTED - expected output. • ENTER • DELAY - delay between commands' execution. • DN - directory service DN (Distinguished Name) parameter • FILTER - directory service user filter.
delay	int	Delay after running the command before executing the next one. Required if command_type==DELAY
command	text	Required if command_type==INPUT.
expected	text	Required if command_type==EXPECTED
comment	text	Optional commentary.

Table 3: VariablesModel

Parameter	Type	Description
id	bigint	Object identifier.
name	text	Required.
object_property	text	
encrypt	bool	<ul style="list-style-type: none"> • true - encrypt variable value, • false - store variable value in plain text.
description	text	
object_type	text	
required	bool	<ul style="list-style-type: none"> • true - specifying this value is required, • false - specifying this value is not required.

Table 4: account_password_changer

Parameter	Type	Description
id	bigint	Object identifier.
position	int	Password changer position in execution queue.
account	bigint	Account identifier.
password_changer	bigint	Password changer identifier
timeout	int	Script's execution time limit.
accountvariable_set		

Table 5: accountvariable_set

Parameter	Type	Description
id	bigint	Object identifier.
password_changer_variable	bigint	
value	text	Variable value.
account_id	bigint	Account identifier.
server_id	bigint	Server identifier.
account_password_change	bigint	
server_address_id	bigint	

11.2 Creating a password changer

Request

Method	POST
Path	/api/system/password_changers
Headers	Content-Type: Application/JSON
Body	PasswordChangerModel

Response

Status	201 CREATED
Headers	Content-Type: Application/JSON
Body	PasswordChangerModel
Description	Object successfully created. Resultant object's attributes are included in response body.

Response

Status	400 BAD REQUEST
Headers	Content-Type: Application/JSON
Body	ValidationErrors
Description	Validation didn't pass.

Example:

```
curl -k -X POST -H "Content-Type:application/json" https://10.0.150.150/api/system/
↪password_changers?sessionId=kzruk5sg8g41kkdsf868q9kikiify0lz8 -d '{"name":"exemplary_
↪password_changer","timeout":300,"transport":"Telnet","changer_type":"verify",
↪"variables":[{"name":"transport_host","description":null,"encrypt":false,"required
↪":true,"object_type":"fudo_server_address_property","object_property":"host"},{"name
↪":"transport_port","description":null,"encrypt":false,"required":false,"object_type
↪":"fudo_server_property","object_property":"port"},{"name":"transport_bind_ip",
↪"description":null,"encrypt":false,"required":false,"object_type":"fudo_server_
↪property","object_property":"bind_ip"}],"commands":[{"command":"command 1 %
↪%transport_bind_ip%", "expected":null,"delay":null,"command_type":"INPUT"}, {"command
↪":"command 2 %%transport_port%%", "expected":null,"delay":null,"command_type":"INPUT
↪"}, {"command":"command 3 %%transport_host%%", "expected":null,"delay":null,"command_
↪type":"INPUT"}]}'
```

11.3 Retrieving password changers list

Request

Method	GET
Path	/api/system/password_changers

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 6: Pagination parameters

page	int
page_size	int

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	[PasswordChangerModel, ...]

Example:

```
curl -k -X GET "https://10.0.150.150/api/system/password_changers?
↪sessionid=bxku41a50hadxnctdv2s21ebleampn99"
```

11.4 Retrieving a password changer

Request

Method	GET
Path	/api/system/password_changers/id

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	PasswordChangerModel

Response

Status

404 NOT FOUND

Not found.

Example:

```
curl -k -X GET "https://10.0.150.150/api/system/password_changers/1?
↪sessionid=bxku41a50hadxnctdv2s21ebleampn99"
```

11.5 Modifying password changers

Request

Method

PUT

Path

/api/system/password_changers/id

Response

Status

200 OK

Headers

Content-Type: Application/JSON

Body

PasswordChangerModel

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

PasswordChangerModel

Response

Status	404 NOT FOUND
Description	Object not found.

Example:

```
curl -k -X POST -H "Content-Type:application/json" https://10.0.150.150/api/system/
↪password_changers/68719476747?sessionId=kzwwk5sg8g41kkdsf868q9kikifgy0lz8 -d '{"name
↪": "New name", "timeout":300, "transport": "Telnet", "changer_type": "verify", "variables
↪": [{"name": "transport_host", "description": null, "encrypt": false, "required": true,
↪"object_type": "fudo_server_address_property", "object_property": "host"}, {"name":
↪"transport_port", "description": null, "encrypt": false, "required": false, "object_type":
↪"fudo_server_property", "object_property": "port"}, {"name": "transport_bind_ip",
↪"description": null, "encrypt": false, "required": false, "object_type": "fudo_server_
↪property", "object_property": "bind_ip"}], "commands": [{"command": "command 1 %
↪%transport_bind_ip%", "expected": null, "delay": null, "command_type": "INPUT"}, {"command
↪": "command 2 %%transport_port%%", "expected": null, "delay": null, "command_type": "INPUT
↪"}, {"command": "command 3 %%transport_host%%", "expected": null, "delay": null, "command_
↪type": "INPUT"}]}'
```

11.6 Deleting a password changer

Request

Method	DELETE
Path	/api/system/password_changers/id

Response

Status	204 NO CONTENT
--------	----------------

Response

Status	404 NOT FOUND
Description	Object not found.

Example:

```
curl -k -X DELETE https://10.0.150.150/api/system/password_changers/68719476746?
↪sessionid=kzwk5sg8g41kkdsf868q9kikifgy0lz8
```

11.7 Retrieving account-password changers assignments list

Request

Method	GET
Path	/api/system/account_password_changers

Note: Results pagination

Every GET request, which returns a collection of objects can be optionally paginated. To achieve it add a pagination parameter to the request path:

```
/api/system/objects?page=3&page_size=10
```

Table 7: Pagination parameters

page	int
page_size	int

Response

Status	200 OK
Headers	Content-Type: Application/JSON
Body	[AccountSafeAssignmentModel, ...]

Example:

```
curl -k -X GET "https://10.0.150.150/api/system/account_password_changers?
↪sessionid=kzwk5sg8g41kkdsf868q9kikifgy0lz8"
```

11.8 Adding a password changer to account

Request

Method

POST

Path

/api/system/account_password_changers

Body

account_password_changer

Response

Status

201 CREATED

Headers

Content-Type: Application/JSON

Body

AccountPasswordChanger

Response

Status

400 BAD REQUEST

Headers

Content-Type: Application/JSON

Body

ValidationErrors

Response

Status

404 NOT FOUND

Example:

```
curl -k -X POST https://10.0.8.89/api/system/account_password_changers?
↪sessionid=d1ldo47q89tn8s9i1bz6h3fug2yqzot4 -d'
{
  "account": 1992864825347,
  "accountvariable_set": [
    {
      "account_id": 1992864825347,
      "password_changer_variable": 109,
      "server_address_id": null,
      "server_id": null,
      "value": null
    },
    {
      "account_id": 1992864825347,
      "password_changer_variable": 110,
      "server_address_id": null,
      "server_id": null,
      "value": null
    },
    {
      "account_id": null,
      "password_changer_variable": 102,
      "server_address_id": null,
      "server_id": 1992864825347,
      "value": null
    },
    {
      "account_id": 1992864825347,
      "password_changer_variable": 103,
      "server_address_id": null,
      "server_id": null,
      "value": null
    },
    {
      "account_id": null,
      "password_changer_variable": 101,
      "server_address_id": 1992864825351,
      "server_id": null,
      "value": null
    },
    {
      "account_id": 1992864825347,
      "password_changer_variable": 106,
      "server_address_id": null,
      "server_id": null,
      "value": null
    },
    {
      "account_id": null,
      "password_changer_variable": 107,
      "server_address_id": null,
      "server_id": 1992864825347,
      "value": null
    },
    {
      "account_id": 1992864825347,
```

(continues on next page)

(continued from previous page)

```
    "password_changer_variable": 104,  
    "server_address_id": null,  
    "server_id": null,  
    "value": null  
  },  
  {  
    "account_id": null,  
    "password_changer_variable": 105,  
    "server_address_id": null,  
    "server_id": null,  
    "value": "base1"  
  }  
],  
"password_changer": 13,  
"position": 0,  
"timeout": 300  
'}]'
```

11.9 Deleting an account-password changer assignment

Request

Method

DELETE

Path

/api/system/account_password_changers/id

Response

Status

204 NO CONTENT

Response

Status

404 NOT FOUND

Example:

```
curl -k -X DELETE https://10.0.150.150/api/system/account_password_changers/  
↪68719476738?sessionId=yqwcj5slxvct2i87zivdammynl27e7k
```

CHAPTER 12

AAPM communication

Description pending.

13.1 Logging in and retrieving session key

```
curl -k -X POST -H "Accept:application/json" -H "Content-Type:application/json" ↵  
↪https://fudo.whl/api/system/login -d '{"username": "api_user", "password": "api_  
↪password"}'
```

```
{"sessionid": "oz2jfky042kz7d3zc2gos1ahxouehk3"}
```

13.2 Fetching users list

```
curl -k -X GET -H "Accept:application/json" -H "Content-Type:application/json"  
↪"https://fudo.whl/api/system/users?sessionid=oz2jfky042kz7d3zc2gos1ahxouehk3&page_  
↪size=2&page=1"
```

```
{  
  
"count":110,"next":"https://fudo.whl/api/system/users?page=2&page_size=2&  
↪sessionid=oz2jfky042kz7d3zc2gos1ahxouehk3", "  
previous":null,"results":  
  
[{"id":688817234205737171,"email":"","language":"en","blocked":true,"reason":"","name  
↪":"Administrator","full_name":"","organization":null,"phone":"","ad_domain":"","  
↪"ldap_base":"","failures":0,"external_sync":false,"valid_since":"0001-01-01T00:00  
↪","valid_to":"9999-12-31T23:59:59.999999","role":"user"},  
  
{"id":688817234205737275,"email":"","language":"en","blocked":false,"reason":"","name  
↪":"User20000","full_name":"test user","organization":"test organization","phone":"","  
↪"ad_domain":"test.ad","ldap_base":"","failures":0,"external_sync":false,"valid_since  
↪":"2017-05-19T09:23:14","valid_to":"2017-07-18T09:23:14","role":"user"}]  
  
}
```


13.3 Adding a user

```
curl -X POST -H "Accept:application/json" -H "Content-Type:application/json" https://
↳ fudo/api/system/users?sessionId=oz2jfkY042kz7d3zc2gos1ahxouxehk3 -d '{"role": "user
↳ ", "name": "test-user", "language": "en"}'

{"id":688817234205737277,"email":"","language":"en","blocked":false,"reason":"","name
↳ ":"test-user-admin","full_name":"","organization":null,"phone":"","ad_domain":"","
↳ "ldap_base":"","failures":0,"external_sync":false,"valid_since":"0001-01-01T00:00:00
↳ ","valid_to":"9999-12-31T23:59:59.999999","role":"user"}
```

13.4 Setting user authentication method - static password

```
curl -k -X POST -H "Accept:application/json" -H "Content-Type:application/json"
↳ https://fudo/api/system/users/688817234205737277/methods?
↳ sessionId=oz2jfkY042kz7d3zc2gos1ahxouxehk3 -d '{"type": "password", "secret": "test-
↳ password", "position":0}'

{"id":688817234205751316,"needs_change":false,"position":0,"type":"password"}
```

13.5 Setting user authentication method - SSH key

```
curl -k -X POST -H "Accept:application/json" -H "Content-Type:application/json"
↳ https://fudo.whl/api/system/users/688817234205737277/methods?
↳ sessionId=lqt6wpz2z8zatcsh8fnigv4l1zxd6bx2 -d '{"type": "sshkey", "secret": "ssh-
↳ rsa
↳ AAAAB3NzaC1yc2EAAAADAQABAAQDS7xsCHfD+bnAoKytzwnxCmTfGEvUuAJTjYOWTZugtodbCh1poTBYuQ8.
↳ ..
↳ ..HpWyBUYVcN80b7Y5bTq8CZO+iPTFKBfzMILu3VDyBRvjuLhCgz5f1UPhbMWE2/
↳ WpRSFjk5wQ1PR33FMZWnSnxS0Q8qkJqIrF+9mkz2fu/
↳ oSQC0kz0IIqrPUYQoM1YKxGslrSyT+M7TenDxyDsJgBhsyjosLXjbIbwLI/HnPgL...
↳ ..TproWWh/wHS2faPHRH1DcSlep4SYfSWqNh59FYE+r12hzkpNwaE/
↳ gLEM9XLUyNImQ+bkJ5K0+2dyvu80avg89WD8V2KP7Qn59gcxJCnweQ+wX0+GpCsAL", "position":0}'

{"id":688817234205752136,"needs_change":false,"position":1,"type":"sshkey"}
```

13.6 Fetching user authentication methods list

```
curl -k -X GET -H "Accept:application/json" -H "Content-Type:application/json" https://
↳ fudo.whl/api/system/users/688817234205737277/methods?
↳ sessionId=lqt6wpz2z8zatcsh8fnigv4l1zxd6bx2

{"id":688817234205751316,"needs_change":false,"position":0,"type":"password"},{"id
↳ ":688817234205752136,"needs_change":false,"position":1,"type":"sshkey"}]
```

13.7 Deleting user authentication method

```
curl -k -X DELETE -H "Accept:application/json" -H "Content-Type:application/json"␣  
↪https://fudo.whl/api/system/users/688817234205737277/methods/688817234205751316?  
↪sessionId=lqt6wpz2z8zaticsh8fnigu4l1zxd6bx2
```

13.8 Changing user login

```
curl -k -X PATCH -H "Accept:application/json" -H "Content-Type:application/json"␣  
↪https://fudo.whl/api/system/users/688817234205737277?  
↪sessionId=lqt6wpz2z8zaticsh8fnigu4l1zxd6bx2 -d '{"name": "new-user"}'  
  
{  
  "id": "688817234205737277",  
  "email": "",  
  "language": "en",  
  "blocked": false,  
  "reason": "",  
  "name": "new-user",  
  "full_name": "",  
  "organization": null,  
  "phone": "",  
  "ad_domain": "",  
  "ldap_base": "",  
  "failures": 0,  
  "external_sync": false,  
  "valid_since": "0001-01-01T00:00:00",  
  "valid_to": "9999-12-31T23:59:59.999999",  
  "role": "user"  
}
```

13.9 Blocking user

```
curl -k -X PATCH -H "Accept:application/json" -H "Content-Type:application/json"␣  
↪https://fudo.whl/api/system/users/688817234205737277?  
↪sessionId=lqt6wpz2z8zaticsh8fnigu4l1zxd6bx2 -d '{"blocked": "True"}'  
  
{  
  "id": "688817234205737277",  
  "email": "",  
  "language": "en",  
  "blocked": true,  
  "reason": "",  
  "name": "new-user",  
  "full_name": "",  
  "organization": null,  
  "phone": "",  
  "ad_domain": "",  
  "ldap_base": "",  
  "failures": 0,  
  "external_sync": false,  
  "valid_since": "0001-01-01T00:00:00",  
  "valid_to": "9999-12-31T23:59:59.999999",  
  "role": "user"  
}
```